SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Airtac 3 Mega, Airtac 3 Mega Green

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Temporary spray adhesive
For industrial purposes only

1.3 Details of the supplier of the safety data sheet

Company name:

Airtech International, Inc.
5700 Skylab Road
Huntington Beach, CA 92647
E-mail: airtech@airtechintl.com
Website: www.airtechonline.com
Telephone: +1 714.899.8100
Department responsible for information:
Telephone: +1 714.899.8100
E-mail: airtech@airtechintl.com

Airtech Europe Sarl
Zone industrielle Haneboesch
L–4562 Differdange
Luxembourg
Website: www.airtech.lu
Telephone: +352 582.282
Department responsible for information:
Telephone: +352 582.282
E-mail: sales@airtech.lu

Airtech Advanced Materials UK Ltd.
The Causeway
Broadway Business Park
Chadderton, Oldham
OL9 9XD United Kingdom
Website: www.airtech-amg.co.uk
Telephone: +44 161.947.1610
Department responsible for information:
Telephone: +44 161.947.1610
E-mail: sales@airtech-amg.co.uk

Airtech Asia Ltd.
No. 161 of Anyuan Rd
Chagugang County
Wuqing District
301721, Tianjin, P.R. China
Website: www.airtech.asia
Telephone: +86 22 8862 9800
Telefax:: +86 22 8862 9900
Department responsible for information:
Telephone: +86 22 8862 9800
E-mail: airtech.asia@airtechasia.com.cn

1.4 Emergency telephone number

CHEMTREC EMERGENCY PHONE:
International: +1 703-741-5970

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Aerosol 1; H222; H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
STOT SE 3; H336	May cause drowsiness or dizziness.
Aquatic Chronic 2; H411	Toxic to aquatic life with long lasting effects.
(EUH066)	Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Labelling (CLP)



Signal word: **Danger**

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing spray.
P273	Avoid release to the environment.
P391	Collect spillage.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling:

Contains
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
n-Pentane
Hydrocarbons, C6, isoalkanes, < 5% n-hexane

2.3 Other hazards

Heating will lead to pressure increase: Danger of bursting and explosion.
In use, may form flammable/explosive vapour-air mixture.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

The product contains no components classified as PBT or as vPvB at concentrations of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture containing the substances listed below:

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119486291-36-xxxx list no. 926-605-8 CAS 64742-49-0	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane Flam. Liq. 2; H225. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411. (EUH066).	30 - 60 %
REACH 01-2119459286-30-xxxx EC No. 203-692-4 CAS 109-66-0	n-Pentane Flam. Liq. 1; H224. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411. (EUH066).	< 10 %
REACH 01-2119484651-34-xxxx list no. 931-254-9 CAS 64742-49-0	Hydrocarbons, C6, isoalkanes, < 5% n-hexane Flam. Liq. 2; H225. Skin Irrit. 2; H315. STOT SE 3; H336. Asp. Tox. 1; H304. Aquatic Chronic 2; H411.	< 10 %
EC No. 270-704-2 CAS 68476-85-7	Petroleum gases, liquefied Flam. Gas 1; H220. Press. Gas (Liq.); H280.	20 - 30 %

Full text of H- and EUH-statements: see section 16.

Additional information: Information about Petroleum gases, liquefied:
Contains < 0.1 % 1,3-Butadiene. Here applies the note K.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: If medical advice is needed, have product container or label at hand.

In case of inhalation: Provide fresh air. Put victim at rest and keep warm. Seek medical attention.

Following skin contact: Remove residues with soap and water. Take off contaminated clothing and wash it before reuse. Do not use solvents or thinners. In case of skin reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.

After swallowing: If swallowed, rinse mouth with water (only if the person is conscious). Do not induce vomiting. Danger of aspiration. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.
After resorption: CNS disorders, unconsciousness, pain
Reaction time and coordination may be impaired.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, carbon dioxide, extinguishing powder

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours form potentially explosive mixtures with air. Heavier than air, they proceed at floor level and may backflash over great distances when ignited.
In case of fire may be liberated: Nitrogen oxides (NOx), traces of incompletely burned carbon compounds, carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and full firefighting protective clothing.

Additional information: Container under pressure. Heating will lead to pressure increase: Danger of bursting and explosion.
Cool endangered containers with water spray and, if possible, remove from danger zone.
Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Provide adequate ventilation. Keep unprotected people away. Evacuate area. Do not breathe vapour/aerosol. Avoid contact with skin and eyes. Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion!
In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).
Thoroughly clean surrounding area.
In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out).

Additional information: Take precautionary measures against static discharges.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Do not breathe vapour/aerosol.
Do not open or incinerate, even when empty. Do not spray into flames or on incandescent objects.
Provide good ventilation and/or an exhaust system in the work area. Do not spray into eyes or onto the skin.
Wear appropriate protective equipment. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse.

Precautions against fire and explosion:
Forms explosive mixtures with air. Use only spark proof tools.
Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:
Keep in a cool, well-ventilated place. Keep container dry.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store containers in upright position.

Hints on joint storage: Do not store together with: Strong oxidizing agents, strong alkalis, strong acids

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
109-66-0	n-Pentane	Europe: IOELV: TWA Ireland: 8 hours	3,000 mg/m³; 1,000 ppm 3,000 mg/m³; 1,000 ppm

DNEL/DMEL:
Information about Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (CAS 64742-49-0):
DNEL workers, inhalative, systemic, long-term: 5,306 mg/m³
DNEL workers, dermal, systemic, long-term: 13,964 mg/kg bw/d
DNEL consumers, inhalative, systemic, long-term: 1,131 mg/m³
DNEL consumers, dermal, systemic, long-term: 1,377 mg/kg bw/d
DNEL consumers, oral, systemic, long-term: 1,301 mg/kg bw/d

Information about n-Pentane (CAS 109-66-0):
DNEL workers, inhalative, systemic, long-term: 3,000 mg/m³
DNEL workers, dermal, systemic, long-term: 432 mg/kg bw/d
DNEL consumers, inhalative, systemic, long-term: 643 mg/m³
DNEL consumers, dermal, systemic, long-term: 214 mg/kg bw/d
DNEL consumers, oral, systemic, long-term: 214 mg/kg bw/d

PNEC: Information about n-Pentane (CAS 109-66-0):
PNEC water (freshwater): 230 µg/L
PNEC water (marine water): 230 µg/L
PNEC sewage treatment plant: 3,600 µg/L
PNEC sediment (freshwater): 1.2 mg/kg dw
PNEC sediment (marine water): 1.2 mg/kg dw
PNEC soil: 0.55 mg/kg dw

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.
Take precautionary measures against static discharges.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.
Use combination filter type A/P according to EN 14387.
The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection: Protective gloves according to I.S. EN ISO 374-1.
Glove material: Butyl caoutchouc (butyl rubber) - Layer thickness: > 0.7 mm
penetration time (maximum wearing period): 15 min
During splash contact:
Glove material: Nitrile rubber - Layer thickness: > 0.12 mm
Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to I.S. EN ISO 16321-1.

Body protection: Protective clothing, solvent-resistant.

General protection and hygiene measures:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Separate storage of work clothes. Do not breathe vapour/aerosol.
When using do not eat or drink.
Wash hands before breaks and after work.
Take off contaminated clothing and wash it before reuse. Do not spray into eyes or onto the skin.
When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid Form: Aerosol
Colour:	amber, green
Odour:	Characteristic

Melting point/freezing point:	-40 °C
Boiling point or initial boiling point and boiling range:	-40 - 2 °C (propellant)
Flammability:	Extremely flammable aerosol.
Lower and upper explosion limit:	LEL (Lower Explosion Limit): 1.40 Vol-% (propellant) UEL (Upper Explosive Limit): 10.90 Vol-% (propellant)
Flash point:	<= -60 °C (propellant)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	7 (solution, concentrated)
Kinematic viscosity:	at 20 °C: 100 - 400 mm²/s (liquid)
Viscosity, dynamic:	at 20 °C: 100 - 300 mPa*s (liquid)
Water solubility:	insoluble
Partition coefficient n-octanol/water (log value):	No data available
Vapour pressure:	at 20 °C: 400 - 600 kPa
Density:	at 20 °C: 0.80 g/mL (liquid)
Relative vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	Vapours can form explosive mixtures with air.
Oxidizing characteristics:	not oxidising
Auto-ignition temperature:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Extremely flammable aerosol.
Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Pressurised container: May burst if heated.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

10.5 Incompatible materials

Strong oxidizing agents, strong acids, alkalis

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data.

Serious eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Based on available data, the classification criteria are not met. Repeated exposure may cause skin dryness or cracking.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): STOT SE 3; H336 = May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

11.2 Information on other hazards

Endocrine disrupting properties:

No data available

Symptoms

In case of inhalation: Narcotic effect in case of higher doses or prolonged exposure. Product may cause headaches, dizziness or troubles of the central nervous system. chest pressure, chest pain, cough. Leads to unconsciousness in high concentrations.
In case of ingestion:
Dizziness, headache, weakness. intoxication. Irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract.
After contact with skin: Upon direct contact with skin may cause itching and redness.
After eye contact: Upon direct contact with eyes may cause burning, tearing, redness.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Toxic to aquatic life with long lasting effects.

Information about Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (CAS 64742-49-0):
Fish toxicity:
LL50 Oncorhynchus mykiss: 12 mg/L/96h (OECD 203)
NOEL Oncorhynchus mykiss: 4 mg/L/96h (OECD 203)
Daphnia toxicity:
EL50 Daphnia magna (Big water flea): 17.06 mg/L/48h (QSAR)
NOELR Daphnia magna (Big water flea): 3.818 mg/L/21d (QSAR)
Algae toxicity:
EL50 Pseudokirchneriella subcapitata (green algae), growth rate: 55 mg/L/72h (OECD 201)
EL50 Pseudokirchneriella subcapitata (green algae), biomass: 26 mg/L/72h (OECD 201)
NOEL Pseudokirchneriella subcapitata (green algae): 30 mg/L/72h (OECD 201)

Information about n-Pentane (CAS 109-66-0):
Fish toxicity:
LC50 Oncorhynchus mykiss: 9.87 mg/L/96h
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): 9.74 mg/L/48h

12.2 Persistence and degradability

Further details: No data available

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The product contains no components classified as PBT or as vPvB at concentrations of 0.1% or higher.

12.6 Endocrine disrupting properties

None

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 16 05 04* = Gases in pressure containers (including halons) containing hazardous substances/Aerosol
* = Evidence for disposal must be provided.

Recommendation: Do not open with force or incinerate, even when empty.
Dispose of waste according to applicable legislation. Do not dispose of with household waste. This material and its container must be disposed of as hazardous waste.

Package

Waste key number: 15 01 10* = Packaging containing residues of or contaminated by dangerous substances
* = Evidence for disposal must be provided.

Recommendation: Dispose of waste according to applicable legislation.
Empty carefully and completely, if possible. Handle empty containers with care.
Incineration may cause explosion.

Section 14. Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR:
UN 1950

14.2 UN proper shipping name

ADR/RID: UN 1950, AEROSOLS
IMDG: UN 1950, AEROSOLS (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane), MARINE POLLUTANT
IATA-DGR: UN 1950, AEROSOLS, FLAMMABLE

14.3 Transport hazard class(es)

ADR/RID: Class 2, Code: 5F
IMDG: Class 2, Subrisk -, see SP63
IATA-DGR: Class 2.1





14.4 Packing group

ADR/RID, IATA-DGR: not applicable
IMDG: -

14.5 Environmental hazards

Dangerous for the environment:
Substance/mixture is environmentally hazardous according to the criteria of the UN model regulations.
Marine pollutant: yes

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board:	RID: Kemmler-number 23, UN number UN 1950
Hazard label:	2.1
Special Provisions:	190 327 344 625
Limited quantities:	1 L
EQ:	E0
Package - Instructions:	P207 LP200
Package - Special Provisions:	PP87 RR6 L2
Special provisions for packing together:	MP9
Tunnel restriction code:	D

Sea transport (IMDG)

EmS:	F-D, S-U
Special Provisions:	63 190 277 327 344 381 959
Limited quantities:	See SP277
Excepted quantities:	E0
Package - Instructions:	P207, LP200
Package - Provisions:	PP87, L2
IBC - Instructions:	-
IBC - Provisions:	-
Tank instructions - IMO:	-
Tank instructions - UN:	-
Tank instructions - Provisions:	-
Stowage and handling:	SW1 SW22
Segregation:	SG69
Properties and observations:	-
Segregation group:	none

Air transport (IATA)

Hazard label:	Flamm. gas
Excepted Quantity Code:	E0
Passenger and Cargo Aircraft: Ltd.Qty.:	Pack.Instr. Y203 - Max. Net Qty/Pkg. 30 kg G
Passenger and Cargo Aircraft:	Pack.Instr. 203 - Max. Net Qty/Pkg. 75 kg
Cargo Aircraft only:	Pack.Instr. 203 - Max. Net Qty/Pkg. 150 kg
Special Provisions:	A145 A167 A802
Emergency Response Guide-Code (ERG):	10L

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - EC member states

Volatile organic compounds (VOC):

42- 43%

Labelling of packaging with <= 125mL content



Signal word: **Danger**

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: Physical hazards: Code P3a,
Quantity threshold 150 000 kg / 500 000 kg
Environmental hazards: Code E2, Quantity threshold 200 000 kg / 500 000 kg

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: P3a, E2
Use restriction according to REACH annex XVII, no.: 3, 40

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Classification procedure:
Physical hazards: on basis of test data
Health hazards, environmental hazards: calculation method

Wording of the H-phrases under paragraph 2 and 3:

H220 = Extremely flammable gas.
H222 = Extremely flammable aerosol.
H224 = Extremely flammable liquid and vapour.
H225 = Highly flammable liquid and vapour.
H229 = Pressurised container: May burst if heated.
H280 = Contains gas under pressure; may explode if heated.
H304 = May be fatal if swallowed and enters airways.
H315 = Causes skin irritation.
H336 = May cause drowsiness or dizziness.
H411 = Toxic to aquatic life with long lasting effects.
EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change:
Changes in section 2: labelling
Changes in section 3: Composition/information on ingredients
Changes in section 9: physical and chemical properties
General revision

Department issuing data sheet:
see section 1: Department responsible for information

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aerosol: Aerosol
Aquatic Chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Asp. Tox.: Aspiration toxicity
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
CNS: Central Nervous System
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EC50: Effective Concentration 50%
EL50: Effective loading rate 50%
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
EU: European Union
Flam. Gas: Flammable gases
Flam. Liq.: Flammable liquid
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LEL: Lower Explosion Limit
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
NOEL: No Observed Effect Level
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
Press. Gas: Gases under pressure
QSAR: Quantitative Structure-Activity Relationship
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Skin Irrit.: Skin irritation
STOT SE: Specific target organ toxicity - single exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
UN: United Nations
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

This data sheet cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, and which additional precautions may be necessary. All health and safety information contained in this data sheet should be provided to your employees and customers. It is your responsibility to develop appropriate workplace instructions and training programmes for employees.

As the conditions and methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this product. The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. All statements or suggestions are made without warranty, expressed or implied, regarding accuracy of information, the hazards connected with the use of the product or the results to be obtained from the use thereof.